TYPICAL undergrand copper twis par network telephone exchange ,,





Cabling of homes for telecommunication , a completed guide to home cabling



Possible fault due coming of the telephone voice port inside the ntd ,

Fault due to switch relay connect in mode 3

Basic home networking system typical cabling arragemnt and connector for ftt , typical telephonic and date service connect





Legend :

Modulator socket CCP

Modulator FTT

Coaxial sock NTD

Coaxial plui PC

OPTIC



Canal of transmission gsm interval time area 577us signal terminology



Wave electromagnetic plane impedance caracteris area ,,E/H=377 ohm







Decimal relay rotational test , duplicattest



Time device

A switch line finder respons at pilote final , connect engineering

-B . Switch final connect

Signal controller , send impulse , etepping relays , interconnector , selector ,pilote ,switch ,,,

Div1 dv 2 div 3 , dv4

10. sequence relais , line , cut off, line , decimal control , direct register in the group in which the calling division starter research



Scale method , quadrille

za

V3
zin

V2



B= Zin /zin 1+z2, sq 2

Consummation aun of network unity , captor , can unity stockage , emitor

Polyphaser emitor



Emettor a

Module phase Psk ,

M(t)=cos(wot+fi.o)

Sin a(t)=0 then m ot+k)g(kt

Modulation phase shift keying signal module psk ,

m(t)=sum = infi to k =-infinty .

A.cos(w

Receptor frequence intermediater , heterodyne classe architecture



Telemetr

Video output pentode

Power pentode

Power pentode

Philips tv communication I out connector



X(t)

Q(i)

Ir(t)=Vrfcos(w0t)=I(t)variation V1

Qr=(t)Vrf.sin(wot)=Q(t)+variation V2

Insulation in receptor conversion case we cree out mixage voice land Q, voltage 2 voice qadra insulation mean level power block in case of component

Emettor/receptor low vehicle



antenna





Circuit resonance , degeneration inductive ,,





Completed plan of position

Address installation	Property	Installation	Organism control system	Controllogic	

Control organism file component installation device system installation low test , high voltage

-radio-technical

Power amplificatory tv sound basic oscillator line petode tube Characteristic
1. Eat 2. Indirect cathode insulated wire / vi 6,3v 3. Source wire v-10.3 4. Use condition nominal rms 5. Voltage anode va -170-250v 6. Voltage grille vg -170-250 7. Voltage 0v 8. Current 9. Coefficient amplificatory k 10. Resistor internal internal ,0,2 –4,6v 11. Capactity grill cg – 14,7 pf 12. Capacity anode ca 0,4 pf 13. Capacity anode grille less 0,6 pf Vslue limite Peek voltage anode vap max 7 kv


Linear measure
control framework
system log activity
energy power ,
Register
am
volt
va
cos
kwha
kvarh


Emettor
Receptor
Synchro
system